

Dixell Ice Merchandiser					
param	description	value	param	description	value
<b>Set</b>	<b>Thermostat set point</b>	<b>7</b>	dFd	Display during Defrost	if
<b>HY</b>	<b>Thermostat Differential</b>	<b>3</b>	dAd	Max display delay after defrost	30
<b>LS</b>	<b>Lower Set Point</b>	<b>5</b>	Fdt	Drip time after defrost end	0
<b>US</b>	<b>Upper Set Point</b>	<b>15</b>	dPo	First defrost after startup	N
<b>Ot</b>	<b>Offset Room Temp</b>	<b>0</b>	dAF	Defrost delay after Fast Freeze	0
<b>P2P</b>	<b>2nd Probe Present</b>	<b>Y</b>	ALc	Alarm Configuration	Ab
<b>OE</b>	<b>Evaporator Probe Cal</b>	<b>0</b>	ALU	Alarm Upper (max alarm)	302
<b>OdS</b>	<b>Output delay @ Startup</b>	<b>0</b>	ALL	Alarm Lower (minimum alarm)	-58
<b>AC</b>	<b>Anti-Cycle (min off after cycle)</b>	<b>2</b>	ALd	Alarm Delay (min)	59
<b>CCt</b>	<b>Comp Continuous time (Fast Freeze)</b>	<b>0</b>	dAO	Alarm Delay at startup (hrs)	1.3
<b>COn</b>	<b>Compressor ON time (probe failure)</b>	<b>15</b>	!1P	Digital input polarity	CL
<b>COF</b>	<b>Compressor OFF (probe failure)</b>	<b>30</b>	!1F	Digital input configuration	EAL
<b>CF</b>	<b>°C /°F</b>	<b>F</b>	did	Digital input alarm delay	5
<b>rES</b>	<b>Resolution 0.0°C (only °C)</b>	<b>in</b>	Nps	# of activation of pressure switch	15
<b>Lod</b>	<b>Probe displayed</b>	<b>P1</b>	odc	Compressor status w/ open door	no
<b>tdF</b>	<b>Defrost Type</b>	<b>EL</b>	PbC	Probe Selection PTC/NTC	NTC
<b>dtE</b>	<b>Defrost Termination Temp</b>	<b>48</b>	dP1	Room probe display	-
<b>IdF</b>	<b>Interval between Defrosts</b>	<b>12</b>	dP2	Evap probe display	-
<b>MdF</b>	<b>(Maximum) length of Defrost</b>	<b>30</b>	rEL	Software release	4.0
<b>dSd</b>	<b>start defrost delay</b>	<b>0</b>	Ptb	Map code	-